

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A magnetic head assembly to record servo signals, that serves for ~~positing~~ positioning of data recording magnetic heads and data reproducing magnetic heads, on magnetic tapes comprising:

a servo signal recording head ~~of which~~ wherein a sliding surface of said servo signal recording head has a magnetic gap embedded thereon in order to record said servo signals onto a the magnetic tape,

a guide block which is set adjacent to a position of up-stream of a line of said magnetic tape passing said servo signal recording head and is slightly set back from said sliding surface of said servo signal recording head so that said magnetic tape slides on an edge of said servo signal recording head thereof and on an outer edge of said guide block.

2. (currently amended): A magnetic head assembly to record servo signals, that serves for ~~positing~~ positioning of data recording magnetic heads and data reproducing magnetic heads, on magnetic tapes comprising:

a servo signal recording head ~~of which~~ wherein a sliding surface of said servo signal recording head has a magnetic gap embedded thereon in order to record said servo signals onto a the magnetic tape,

a guide block which is set adjacent to a position of down-stream of a line of said magnetic tape passing said servo signal recording head and is slightly set back from said sliding surface of said servo signal recording head so that said magnetic tape slides on an edge of said servo signal recording head thereof and on an outer edge of said guide block.

3. (currently amended): A magnetic head assembly to record servo signals, that serves for ~~positioning~~positing of data recording magnetic heads and data reproducing magnetic heads, on magnetic tapes comprising:

a servo signal recording head ~~of which~~wherein a sliding surface of said servo signal recording head has a magnetic gap embedded thereon in order to record said servo signals onto ~~the~~ magnetic tape,

two guide blocks of which one guide block is set adjacent to a position of up-stream of a line of said magnetic tape passing said servo signal recording head, the other guide block is set adjacent to a position of down-stream of a line of said magnetic tape passing said servo signal recording head and both guide blocks are slightly set back from said sliding surface of said servo signal recording head so that said magnetic tape slides on an each edge of said servo signal recording head thereof and on an outer edge of each said guide blocks.

4. (currently amended): A magnetic head assembly according to Claim 1,

wherein a ~~lap-wrap~~ angle  $\theta 1$  between said sliding surface of said recording head and a plane surface formed by ~~an-the~~ edge of said servo signal recording head and said outer edge of said guide block is in a range of 1.0 to 6.0 degrees.

5. (currently amended): A magnetic head assembly according to Claim 2,  
wherein a ~~lap-wrap~~ angle  $\theta 1$  between said sliding surface of said recording head and a plane surface formed by ~~an-the~~ edge of said servo signal recording head and said outer edge of said guide block is in a range of 1.0 to 6.0 degrees.

6. (currently amended): A magnetic head assembly according to Claim 3,  
wherein a ~~lap-wrap~~ angle  $\theta 1$  between said sliding surface of said recording head and a plane surface formed by ~~an-each~~ edge of said servo signal recording head and said outer edge of each said guide block is in a range of 1.0 to 6.0 degrees.

7. (currently amended): A magnetic head assembly according to Claim 1,  
wherein said guide block ~~is,~~has at least at a portion of said outer edge; made of a material which has hardness of more than 1200 Vickers hardness.

8. (currently amended): A magnetic head assembly according to Claim 2,  
wherein said guide block ~~has,~~is, at least at a portion of said outer edge; made of a material which has hardness of more than 1200 Vickers hardness.

9. (currently amended): A magnetic head assembly according to Claim 3,  
wherein each said guide block ~~has~~, at least at a portion of said outer edge, made of a  
material which has hardness of more than 1200 Vickers hardness.

10. (Original): A magnetic head assembly according to Claim 1,  
wherein said guide block is made of a material of  $\text{Al}_2\text{O}_3 \cdot \text{TiC}$ .

11. (Original): A magnetic head assembly according to Claim 2,  
wherein said guide block is made of a material of  $\text{Al}_2\text{O}_3 \cdot \text{TiC}$ .

12. (currently amended): A magnetic head assembly according to Claim 3,  
wherein each said guide block is made of a material of  $\text{Al}_2\text{O}_3 \cdot \text{TiC}$ .

13. (Original): A magnetic head assembly according to Claim 1,  
wherein said guide block is surface-finished for hardening.

14. (Original): A magnetic head assembly according to Claim 2,  
wherein said guide block is surface-finished for hardening.

15. (currently amended): A magnetic head assembly according to Claim 3,

wherein each said guide block is surface-finished for hardening.

16. (currently amended): A magnetic tape servo writer having a magnetic head assembly according to Claim 1,

wherein another ~~lap~~wrap angle  $\theta_2$  between said ~~a~~ plane surface formed by ~~an~~the edge of said servo signal recording head and said outer edge of said guide block and a plane formed by ~~an~~the outer edge of said guide block and an edge of a tape guide which is added to said guide block along a passing line of said magnetic tape is 0.5 to 2.0 degrees.

17. (currently amended): A magnetic tape servo writer having a magnetic head assembly according to Claim 2,

wherein another ~~lap~~wrap angle  $\theta_2$  between said ~~a~~ plane surface formed by ~~an~~the edge of said servo signal recording head and said outer edge of said guide block and a plane formed by ~~an~~the outer edge of said guide block and an edge of a tape guide which is added to said guide block along a passing line of said magnetic tape is 0.5 to 2.0 degrees.

18. (currently amended): A magnetic tape servo writer having a magnetic head assembly according to Claim 3,

wherein another ~~lap~~wrap angle  $\theta_2$  between said plane surface formed by ~~an~~the edge of said servo signal recording head and said outer edge of each said guide block and a plane formed

by ~~an~~ the outer edge of each said guide block and an edge of a tape guide which is added to each said guide block along a passing line of said magnetic tape is 0.5 to 2.0 degrees.

19. (new): A magnetic head assembly according to Claim 1, wherein the magnetic tape comes into contact with only the outer edge of the guide block.

20. (new): A magnetic head assembly according to Claim 1, wherein the magnetic tape slides on the sliding surface of the servo signal recording head.

21. (new): A magnetic head assembly according to Claim 1, wherein the magnetic tape is not parallel to a surface of the guiding block.

22. (new): A magnetic head assembly according to Claim 1, wherein the recording head includes a planar surface as the sliding surface and wherein the guide block is displaced from the planar surface, the guide block having a guide block planar surface substantially parallel to the planar sliding surface.

23. (new): A magnetic head assembly according to Claim 1, wherein the edge of said servo signal recording head and the outer edge of said guide block are chamfered.